

Auto body repair and paint shop



Revised: May 2017

Environmental area	Criterion no.	Statute	Criterion text
System criteria	1924		The enterprise shall seek out services that take consideration of the environment and that comply with laws and regulations. An HSE declaration shall be provided by all major service suppliers.
Working environment	14	§	The employer shall ensure that material safety data sheets for hazardous chemicals used in the enterprise be made available to the employees and that the employees are familiar with and understand their content. Employers have a duty to create a substance database with material safety data sheets for hazardous chemicals.
Working environment	46	§	The enterprise shall have an occupational health service, pursuant to Regulations of 6 December 2011 no. 1355 concerning organisation, management and employee participation, section 13-1. The occupational health service shall be approved pursuant to Regulations of 6 December 2011 no. 1360, Regulations concerning administrative arrangements within the area of application of the Working Environment Act (Administrative Arrangements Regulations), chapter 2.
Working environment	47	§	Sufficient, appropriate, high-quality protection equipment shall be provided in compliance with Regulations of 6 December 2011 no. 1355 concerning organisation, management and employee participation, chapter 15.
Working environment	48		First aid courses shall be provided to all employees. Refresher courses shall be provided at least every three years.
Working environment	1929		The enterprise shall have explosion protection documentation and zone maps, and potentially explosive atmospheres shall be clearly marked with hazard warning signs.
Working environment	1930		Measurements shall be conducted of breathing air and/or compressed air used for protective masks. Such measurements shall be conducted once annually.
Working environment	1931		Maintenance and service plans for spray booths shall be monitored in accordance with the manufacturer's recommendations. Manuals, operating instructions and guidance shall be readily available to users and close at hand.
Working environment	1932		Preparation areas shall have adequate shielding, ventilation and extraction systems, and breathing air (in connection with applying primers) shall be available.
Working environment	1933		Ventilation and extraction systems in mixing rooms shall be sufficient, given the major health risk represented by paint products.
Procurement	432	§	The enterprise shall not use or sell products containing chemicals that are hazardous to health or the environment, in accordance with the Product Regulations, the List of Priority Substances and the Candidate List (REACH Regulation). The enterprise shall evaluate applying the substitution principle, in accordance with the Product Control Act, section 3a.
Procurement	990		Chemical suppliers/manufacturers shall provide documentation/declarations verifying that chemicals comply with applicable legislation, such as the Product Control Act, the CLP Regulations, the Product Regulations, the REACH regulation, the Regulations relating to approval of biocides and biocidal products, and the Regulations relating to the declaration of chemicals to the Product Register. Furthermore, substances that appear on the national List of Priority Substances and the Candidate List in REACH shall not be included in chemicals or have the listed properties. Alternative documentation such as accredited test laboratories, the Nordic Swan Ecolabel or other labelling schemes or technical material data sheets will suffice.
Energy	203		The enterprise shall record its energy consumption and follow it up at least half-yearly.
Energy	1934		The environmental impacts of alternative energy sources shall be evaluated when investing in new equipment. Heat recovery systems in spray booths shall be evaluated.
Waste	179		Car parts that are included in auto manufacturers' recycling schemes shall be returned. Remaining waste shall be separated at source and properly stored in accordance with laws and regulations.
Emissions to water	44	§	All emission permits (licences) for emissions to soil, water and air shall be documented.
Emissions to water	175	§	The oil content of emissions of oily wastewater shall not exceed 50 mg/l. Prior to emission, oily wastewater shall pass through a sand trap or similar cleaning system designed for a maximum flow rate in accordance with Regulations no. 931 of 1 June 2004 relating to the restriction of pollution, chapter 15.